

## GC Septa

Quality materials for all applications



### BTO Septa

- Low bleed septa - ideal for MS applications
- Excellent mechanical properties
- Maximum temperature 400°C

### TR-Green Septa

- Long injection lifetime
- Low injection port adhesion
- Maximum temperature 400°C

### Marathon Septa

- Pre-pierced for reliable performance
- Up to 400 injections per septa
- Maximum temperature 400°C

### TR-Blue Septa

- General purpose septa
- Easy to penetrate
- Maximum temperature 200-250°C

### Septa

Material	ID (mm)	Cat. No.	Quantity
BTO	9	<b>31303240</b>	50 Pack
BTO	11	<b>31303233</b>	50 Pack
BTO	11.5	<b>31303230</b>	50 Pack
BTO	12.7	<b>31303228</b>	50 Pack
BTO	17	<b>31303211</b>	50 Pack
TR-Green	9	<b>313G3240</b>	50 Pack
TR-Green	11	<b>313G3230</b>	50 Pack
TR-Green	12	<b>313G3228</b>	50 Pack
TR-Green	17	<b>313G3211</b>	50 Pack
Marathon	9	<b>313P3240</b>	50 Pack
Marathon	11	<b>313P3233</b>	50 Pack
Marathon	11.5	<b>313P3230</b>	50 Pack
Marathon	17	<b>313P3211</b>	50 Pack
TR-Blue	9	<b>313B3240</b>	50 Pack
TR-Blue	11	<b>313B3233</b>	50 Pack
TR-Blue	11.5	<b>313B3230</b>	50 Pack
TR-Blue	17	<b>313B3211</b>	50 Pack